

**Specifications**

Model		HCP-80B	HCP-168B	HCP-258B	
Type		Air Jacket	Air Jacket	Air Jacket	
Construction	Chamber Volume (L)	80	170	258	
	Interior Chamber	304 Stainless Steel			
	Exterior Chamber	Cold-rolled steel powder coated			
	Access Port	/	35mm Diameter	35mm Diameter	
	Data Outputs	Remote Alarm Contacts, USB, and Optional 4-20mA			
Dimensions	Net/Gross Weight (approx)	kg	75/100	95/130	110/160
		lbs	165/220	242.5/308.6	297/374
	Interior Dimensions (W*D*H)	mm	400*420*490	490*560*650	570*610*745
		in	15.7*16.5*19.3	19.3*22*25.6	22.4*24.0*29.3
	Exterior Dimensions (W*D*H)	mm	625*684*735	714*812*887	794*867*985
		in	24.6*26.9*28.5	28.1*32*34.9	31.3*34.1*38.8
Packing Dimensions (W*D*H)	mm	695*755*915	760*840*1050	865*940*1135	
	in	27.3*29.7*36.0	29.9*33.1*41.3	34.0*37.0*44.7	
Shelves	Dimensions (W*D)	mm	380*300	473*434	550*484
	Number Standard/Maximum		3/7	3/11	3/13
	Max.load Per Shelf/Total Load	kg	10/30	10/30	10/30
	Construction		Perforated, Adjustable		
Electrical	Rated Voltage Power Supply (V/Hz)		115/60	115/60	115/60
	Nominal Consumption (kw) (Steri-run)		0.07 (0.9)	0.095 (1.4)	0.12 (1.6)
Control	Controller		Microprocessor	Microprocessor	Microprocessor
	Display		7" LCD Screen	7" LCD Screen	7" LCD Screen
CO <sub>2</sub>	Control Accuracy		0.1%	0.1%	0.1%
	Range		0-20%	0-20%	0-20%
	Alarm Range		±0.5%	±0.5%	±0.5%
	Inlet Pressure		12-17Psi (0.8-1.2 Bar)		
	Gas Purity		≥99.5%		
	Sensor		IR	IR	IR
	Recovery Time at 5vol.-%/CO <sub>2</sub> for a 30 Second Door Opening*(min)		4	4	4
	CO <sub>2</sub> Inlet Filter (µm)		<0.2	<0.2	<0.2
Alarms	High/Low Temperature		Y	Y	Y
	Remote Alarm		Y	Y	Y
	Excessive CO <sub>2</sub> Concentration		Y	Y	Y
	Water Shortage		Y	Y	Y
	Sensor Error		Y	Y	Y
	Door Ajar		Y	Y	Y
Temperature Parameter	Control Accuracy (°C)		0.1	0.1	0.1
	Range		Ambient temperature+3-55°C		
	Uniformity (°C)		±0.3	±0.3	±0.3
	Ambient Range (°C)		18-32	18-32	18-32
	Sensor		2PT1000	2PT1000	2PT1000
Recovery Time at 37°C for a 30 Second Door Opening*(min)		4	4	4	
Sterilization Cycle	Cycle Temperature		180°C on internal Surfaces and Shelves		
	Cycle Duration		Under 12 Hours	Under 12 Hours	Under 12 Hours
Humidity	RH (Relative Humidity)		Setting 37°C ≥90%	Setting 37°C ≥90%	Setting 37°C ≥90%
	Humidity Reservoir		Max.1.3L/Min 0.5L	Max.3L/Min 0.5L	Max.3.6L/Min 0.5L
Optional	Hepa Filter		Y	Y	Y
	Pressure Reducing Valve		Y	Y	Y
	RS485		Y	Y	Y
	4-20mA		Y	Y	Y
	The Cylinder Switch		Y	Y	Y
Certification		/	/	/	

Product appearance and specifications are subject to change without notice



**HCP-80B/168B/258B**

**Product Features**

- Uniform and Stable Temperature
- Precise CO<sub>2</sub> Concentration
- 180°C Dry-heat Sterilization
- Fast Environment Recovery

**Qingdao Haier Biomedical Co.,Ltd.**

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
Tel: +86-0532-88935593  
Website: www.haiermedical.com



**Haier Biomedical**  
Intelligent Protection of Life Science



## CO<sub>2</sub> Incubator

Haier Biomedical IoT enabled CO<sub>2</sub> incubator with 180°C dry heat sterilisation provides a safe and secure reproducible growth environment for cell cultures.

### IR Sensitive Control of CO<sub>2</sub> Concentration

The new IR sensor with high temperature resistance of 190°C is based on the NDIR measurement principle and uses a silicon MEMS transmitter to replace the traditional light source. It can withstand more than 300 dry heat sterilization cycles with a service life of up to 15 years and control accuracy of  $\pm 0.1\%$ . German IR infrared sensing technology, zero drift, without need for calibration, drift less than 0.3% within 2 years.



### 7-inch Touchscreen

Displays CO<sub>2</sub> concentration and temperature data in real time. 15 years of data can be exported via USB.

### Inner Door


The door ensures the inside of the cabinet is sealed.

### Outer Door

The heated outer door prevents the condensation of the inner door.

### Precise Temperature Control

With six-sided heating based on fuzzy PID control, it has internal dual PT1000 high precision sensors.



6-sided heating sketch

### 304 Stainless Interior



### Adjustable Feet

It can be double stacked.

### 180°C Dry-heat Sterilization

All internal components do not need to be disassembled and do not need separate autoclave sterilization to prevent secondary pollution. Cleaning consumables are not needed, one-button sterilization. German INFRARED CO<sub>2</sub> sensor, NDIR light source technology drift < 0.3% within two years. The unit can withstand sterilization at 180°C with no disassembly and no manual calibration.


### Internal Partition

Safety anti-slip design of pull out shelves.




## Precise and Accurate Temperature Control

Controls the temperature precisely, within  $\pm 0.1^\circ\text{C}$ , with six-sided heating based on the fuzzy PID control principle, to provide a stable temperature to ensure the normal growth of cells throughout their life cycle.




Uniformity of 27 measuring points  $\leq \pm 0.3^\circ\text{C}$




Central consistency point  $\leq \pm 0.1^\circ\text{C}$

## Precise CO<sub>2</sub> Concentration Using New IR Sensor Control Technology

Haier Biomedical's new IR Sensor technology uses NDIR measurement principles and withstands high temperatures of 190°C. The silicon MEMS transmitter can carry out more than 300 dry heat sterilization cycles to extend the service life to 15 years. Built-in temperature and humidity compensation technology reduces the impact of changes of humidity and temperature without the need for calibration after the high temperature sterilization. Five point calibration yields a higher measuring accuracy, sensitivity with less drift.



Silicon-based mems transmitter



Sketch of drift less than 0.3%

## Fast Environment Recovery for Optimal Cell Growth

Adopting active air flow control technology, and based on the fuzzy PID control principle, the parameters can be restored without overshoot. After opening the door for 30 seconds, the temperature and CO<sub>2</sub> concentration can be quickly restored within 4 minutes. Even if multiple users share a CO<sub>2</sub> incubator and frequently open and close the door, the stability and uniformity of the incubator can be ensured.






Illustration of purified airflow



Temperature recovery curve (door open for 30s)




CO<sub>2</sub> concentration recovery curve (door open for 30s)

## 180°C Dry-Heat Sterilization Technology Minimises Contamination

Easy and effective sterilization of microorganisms including bacteria, fungi and microplasma with strong resistance, at 180°C high temperatures without the need for consumables. Simply press the "sterilization key" to activate and complete the sterilization process automatically in just 12 hours.

Delivers sterility level within the chamber of all surfaces to meet WS/T367-2012 standards.

All components are sterilized during the process, there is no need to disassemble internal components (including CO<sub>2</sub> sensors) and decontaminate separately, thus avoiding secondary pollution.



### Sterilization Temperature Profile

Thirty-four points were tested in the working chamber, including glass inner doors and partitions. All regions reached 180°C and maintained for 2 hours.



Ultraviolet disinfection

Cells exposed to bacterial environment



90°C hygrothermal disinfection

Cells exposed to bacterial environment



180°C dry-heat sterilization of haier CO<sub>2</sub> incubator

Pollution-free cell growth environment

## High Efficiency Microbial Filter



The CO<sub>2</sub> inlet is equipped with a high-efficiency microbial filter, with 99.99% filtration efficiency for particles larger than or equal to 0.2µm in diameter. It can effectively filter bacteria and dust particles in the CO<sub>2</sub> gas line to ensure the safety of experimental results.

## Easy to Clean Interior

The working chamber is plasma electro polished, stamped stainless steel with wide-arc, laser welded corners. Bracketless shelving design ensures that it is quick and easy to clean.



## Interactive Intelligent Display with Easy Touch Operation


Touch-sensitive screen with rapid sensing even in rubber gloves. Green indicates normal operational parameters, while a red warning display indicates abnormal, making it easy to view data at a glance. A red warning display and audible buzzer will alarm when water level is low.



Home screen red warning



Real-time display of operation data & real-time display of temperature, for CO<sub>2</sub> concentration and O<sub>2</sub> concentration, and the data during the culture cycle can be viewed at any time.



Announcement function designed for multiple persons to use the same incubator making it clear to all users on important matters.



Operation mode clear management authority: three-levels of authority to ensure the security of data.

## Realtime Monitoring via Optional IoT Module



The IoT module is optional. The information of the setting parameters, operation parameters, operation curves, alarm records and event records is uploaded in real time through IoT cloud platform to ensure real time monitoring of the operation status of the incubator by APP or PC.

## Anti-Condensation Heating System to Reduce Pollution Risk

The door on the CO<sub>2</sub> incubator radiates heat to the inner glass door, effectively preventing the glass door from forming condensation. The possibility of microbial contamination caused by the condensate water is eliminated.

## Intelligent Control of Circulating Air Maintains Uniformity

Automatically adjusts the circulation of the air flow, optimising the air flow to avoid air volatilization of samples and ensuring proper uniformity throughout the chamber.

## Comprehensive Safety Alarm System

The system ensures the safety of experiments and processes by utilizing an independent temperature alarm system, including a sound light and remote reminder. Other alarms include CO<sub>2</sub> concentration, door ajar and water shortage.


## Innovative and User-friendly Design with Attention to Detail



Safe anti-slip design with pull out shelves.



Convenient drainage design




Active heat pipe condensation technology with any condensation directly returning to the reservoir.




Data traceable for 15 years with large storage capacity and data exportable through USB.

## CAD Dimensions



## O<sub>2</sub> Control (Optional) for HCP-168B Only

The nitrogen intake is controlled by the oxygen concentration detected by the oxygen sensor. By filling nitrogen, the oxygen concentration can be controlled in the range of 1-21% and the control accuracy is 0.1%, which can simulate the hypoxic conditions for the research of primary cell, stem cells and embryos.



\*To order the HCP-168B incubator complete with O<sub>2</sub> control module use product code O<sub>2</sub>-HCP-168B.

## Optional Accessories

Name	Picture	Name	Picture
Relief Valve		Water Tray	
HEPA Filter		Oxygen Sensor (only for HCP-168B)	
HEPA Filter Cover		Solenoid Valve (only for HCP-168B)	
Stacking Frame		6 Inner Door (only for HCP-168B)	
Internal partition		3 Inner Door (only for HCP-168B)	
Roller base			